EA630 BEST IN CLASS High performance scalable mobile computer!





Scalable PDA with insane screen to body ratio! Powerful, rugged, multitasking, responsive and scalable device whilst being competitively priced!

The EA630 is impressive with its large 6" HD+ 18:9 display, 80% screen to body ratio design and snappy Qualcomm Snapdragon 636 Octa-core 64-bits 1.8 GHz processor. A large 4000mah battery capacity frees you from the concern of battery draining during your working day. This enterprise mobile computer offers all great enterprise and smartphone features but styled into a scalable design as it comes with a great and unique range of optional accessories - making your work days easier.

Offering the latest OS of Android 9 and upgradable to Android 10, the EA630 also comes with the Google GMS license and AER certification.

It is ideal for a variety of applications in the retail, warehousing, T&L, hospitality, healthcare and field services.



Large screen to body ratio The EA630 screen-to-body ra

The EA630 screen-to-body ratio is a massive 80%. This gives you a big screen in a compact design for easier multitasking (run 2 apps on one screen) and more immersive readability.

High resolution with a bright screen The 6.0" (2160 x 1080 pixel) high brightness readable (450 nits) full HD+ display (18:9) with backlight makes the EA630 extremely user friendly and readable in any environment.

Removable quick charge battery

For businesses a long battery life is essential. The EA630 comes with an easy swappable 4000mAh battery supporting Quick Charge 3.0 technology.

Lightweight and tough

The Unitech EA630 only weights 230g, but is fitted with a Gorilla® 6 Glass touch panel, has a drop resistance of 1.2m (1.5m with optional boot case) and an IP65 rated body to withstand the harshest environments.

Scalability

Thanks to POGO pins on rear- and bottom side, the EA630 has limitless scalability options for accessories such as gun grips and desktop cradles. The EA630 comes with a rich line of professional accessories to customize your working requirements.

External Display via DisplayPort

Use the ethernet 1-slot desktop cradle to connect your EA630, via the Display Port (DP), to an external full-size monitor (can also carry audio, USB, and other forms of data).

All-in-One data collection

The EA630 has an integrated 1D/2D scanning capability, as well as an integrated HF/NFC RFID reader/writer, GPS, and a high-resolution 16MP camera in this compact device.

Extensive range of accessories

Boost the functionality of the EA630 device with Unitech's unique and versatile gun grip accessories to extend your data collection. From standard trigger gun grip to Long Range 2D or RFID gun grip accessory.

unitech



	Operation System			Data capture		
	CPU	Qualcomm Snapdragon		Scanning	Scanner	(Engine: N3603)
		1.8GHz 636 Octa core 64-bit Processor		1D:		I/JAN, GS1 DataBar, Code 39, Code 128,
	Memory	3GB RAM			Code 32,	Code 93, Codabar/NW7, Inter leaved 2 of
	·	32GB Flash				2 of 5, MSI, Trioptic.
	OS	Android 9 with:		2D:	PDF417, I	MicroPDF417, GS1 Composite, Code11,
		GMS (Google Mobile Service) certication			Aztec Co	de, Data Matrix, QR Code, Micro QR Code,
		AER (Android Enterprise Recommended)			Maxi Coc	le, Han Xin Code, <mark>DOT Code</mark> .
	Card Slot	1x Micro SD/TF (max. 256GB)		Postal:	0	t Mail Barcode, Postal-4i, Australian Post,
		2 x Nano Sim				e Post, Netherlands (KIX) Post, Postnet,
	Language Support	English, Simplied Chinese, Traditional Chinese,			Planet Co	
		Japanese, Spanish, German, French, Italian,		OCR:		DCR-B, E13B (MICR).
		Portuguese, Korean and multiple languages		RFID/NFC:	Support H	
	Disalar					y 13.56Mhz
	Display 6" (18:9) Full-HD (2160 x 1080) colour, Ultra sensitive capacitive type					ISO14443-4 (Type A, Type B),
	5 points multi-touch screen, compatible with gloves and support wet					3 standard, Mifare,
		6 glass, Backlight, 450nits.		2D Long Dongo		O/IEC18092).
		giass, Dacklight, 400hts.		2D Long Range:		Gun Grip accessory
	Camera/Photos/Video					ell EX30 Barcode Engine
	Rear: 16MP camera, Auto Focus, LED flash light				Support 5cm~20meters reading distance* (*Depending on width, type and quality of barcode).	
		, Auto Foodo, EED haon light		RFID/UHF:		Gun Grip accessory
	 Audio One speaker (95±3dB @ 10cm), One receiver, Dual noise-cancelling 				6 meters plus reading distance* (*Depends on environment, tags and object).	
	microphones.				(Dopondo (
				Power Source		
	Buttons Side SCAN button x 2 (Left / Right), User-defined function button,			Main battery	Swappable and rechargeable 3.8V 4000mAh Li-polymer battery pack.	
	Volume switch butte	on (+ / -), ON / OFF buttons		Operation	10-12 hours	
					(dependir	ng on the specific environment)
	Indicator			Quick charging	Support QC3.0 with separate power adapter	
	LED, Speaker, Vibra	tor				B type-C port only
	Ormaniation			RTC battery	Real time clock battery	
	Communication USB	LICE2 1 (turse C) support LICE OTC				
	036	USB3.1 (type-C) support USB OTG Support Display Port Mode		Environmental		1090 to 5090
		Ethernet/USB-Host via cradle		Operating tempera		-10°C to +50°C
	OTG	Yes, over USB Type-C		Storage temperatur		-30°C~70°C (without battery) 0°C to 45°C
	POGO PIN	PogoPin backside: Support Gungrip, UHF reader		Charging temperatu Relative humidity	ле	$5\% \sim 95\%$ (non-condensing)
		PogoPin bottom: Charging via cradle		Drop specification		1.2m MIL-STD 810G,
		Electronic switch gun-grip		Drop specification		1.5m with boot case
	WLAN	Wireless LAN 802.11a/b/g/n/ac,		Sealing		IP65
				ocumy		11 00

2.4GHz and 5GHz

IEEE 802.11i WPA2

2 x Nano Sim

B19/B20/B28)

250g (with battery)

SBAS

Bluetooth

GPS

WWAN 4G LTE

Other Sensors

Enclosure

Dimension

Software Support

airwatch by vmware Unitech Europe

Weight

Support 802.11d/e/h/i/k/r/v, fast roaming

Bluetooth® 5.0+ BR/EDR + BLE supported

WCDMA: Band 1, Band 2, Band 5, Band 8

LTE: FDD-LTE (B1/B2/B3/B4/B5/B7/B8/B 12/B17/

AGPS, GPS, GLONASS, Beidou, Galileo, QZSS,

Gyroscope, Light sensor, e-Compress, Proximity

sensor, Accelerometer sensor, SAR sensor

SOTI[®] TeamViewer

Compliant with WEP, WPA and

GSM: 850,900,1800,1900 MHz

TDD-LTE: (B38/B39/B40/B41)

157.4mm×76.4mm×13.9mm

- Regulatory Approvals

CE, FCC, NCC, BSMI, VCCI, CCC, RoHS, CEC, BQB, N-Mark compliance.

Accessories

Quick charge 3.0 EU daptor (via USB type-C cable) USB 3.0 type-C Quick-charging cable USB 2.0 type-C Standard USB cable 9H glass screen protector Protective boot (without hand-strap) Stylus Coiled strap Hand strap (including bracket) Bracket Belt holster (with belt clip) Single Slot Charging cradle Single Slot USB cradle Single Slot Ethernet cradle Power adapter for 1-slot cradles 4 Slots Ethernet cradle 4 Slots Terminal Charging cradle Power adapter for 4-slot cradles 3 Pins Power Cord (EU) for Power Adaptor 3 Pins Power Cord (UK) for Power Adaptor Gun grip standard (version with or without protective boot) Gun grip 2D Long Range (version with or without protective boot) Gun grip UHF RFID (version with or without protective boot)



Tilburg, The Netherlands • Tel.: +31 (0)13 460 9292 • Email: Info@eu.ute.com • Website: http://eu.ute.com • Website: http://eu.ute.com • Specifications subject to change without notice. Copyright 2011 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.